

## General Description

7501 Fast Dry Primer is a fast drying thin, solvent-reduced, penetrating primer for sealing and revitalizing dried-out, absorbent surfaces before applying asphaltic coatings. Fast Dry Primer penetrates porous surfaces and quickly sets to ensure an excellent substrate bond for membranes and coatings. Meets the requirements of CGSB-37-GP-9M and ASTM D41(Type II).

## Uses

Fast Dry Asphalt Primer's main use is for priming absorbent surfaces to improve the bond and provide a tack coat for the application of modified asphalt coatings or sheet membranes.

## Limitations

This is a flammable product and care must be taken to keep away from open flames and provide ventilation to remove fumes. It should not be stored at temperatures more than 50°C or 120°F.

## Physical Properties

Colour	-	Black
Solids	-	55 % minimum
Drying Time	-	Touch dry – 30 min. at 25°C (77°F) Firm dry – 2 hours at 25°C (77°F)
Density	-	0.90 kg per litre (7.5 lb per U.S. gallon)

## Preparation

Surfaces should be clean, dry, and scraped clean of gravel dirt and rough projections.

## Characteristics

7501 is a thin solution and will not freeze. It is applied at a rate of 2.4 - 3.7 L/10m<sup>2</sup> (1/2 - 1 gallon/100ft<sup>2</sup>).

## Application

**Roofs** - Apply by brush, roller, spray at a rate of ¼ -1L/m<sup>2</sup> (½ - 2 gallon/100ft<sup>2</sup>). Use adequate amount without pooling. Let the primer dry before applying asphalt topcoat.

**Foundations** - Apply by brush, roller, or spray at a minimum rate of 0.4 L/m<sup>2</sup> (1gallon/100ft<sup>2</sup>).

A 425-gram spray can will cover approximately 24ft<sup>2</sup> per can.